
454 Universal Snake Tray®

Hand Bendable, Universal Mounting Cable Tray

Snake Tray® has designed the next generation in cable management with a conveyance system that is hand bendable and can be mounted overhead or on walls in one easy-to-install system.





- Loading **Physical Dimensions Dimensions Physical** Cable **Finish Part Number** Height/Length/Width Diameter Volume Capacity Wt CM 454-2-8 3 3/4" x 8' x 2 3/8" 2" 3 si 30 3# G/SS/PC CM 454-4-8 5 3/4" x 8' x 4 3/8" 12 si 120 5# G/SS/PC
- FOR BEST RESULTS IT IS RECOMMENDED THAT SNAKE TRAY BE ANCHORED EVERY FOUR (4) TO FIVE (5) FEET

7 3/4" x 8' x 6 3/8"

CABLE CAPACITY BASED ON 50% FILL AS PER NEC ARTICLE 392.9B 0.25 OD FINISHES: MECHANICALLY APPLIED GALVANIZED FINISH (G), STAINLESS STEEL (SS), POWDER COATED (PC)

- Hand bendable (No cutting required!)
- Protects and secures both fiber and copper cables in all directional plains
- Maintains the proper bend radius for optimal performance
- Built-in mounting rings can be attached either overhead or on a wall
- Designed for easy pulling or loading cables from the side
- Nests together for low cost shipping and material handling
- Self limiting cable count for code compliant conveyance of power over ethernet systems

LOADING CAPACITY

CM 454-6-8

Universal Series Snake Tray			Cable Fill (50% fill)** - CAT			Support Span Lbs/Ft (max)			
Part Number	Height x Width	Area (in2)	5e Cables*	6 Cables*	6A Cables*	4'-0"	5'-0"	6'-0"	8'-0"
CM 454-2-8	2"	6.3	44	30	23	6	5	4	***
CM 454-4-8	4"	12.5	180	120	90	26	20	16	***
CM 454-6-8	6"	28	403	288	200	58	46	35	***

28 si

260

7 ½ #

G/SS/PC

- * CAT5e 4 pair PL approximated at .19 in² in diameter, CAT 6 4 pair PL cable approximated at .25 in² in diameter and CAT 6 A 4 pair PL approximated at .30 in²
- ** Allowable fill ratios are based on the NEC rule that the cross sectional area of all the cable installed in the cable tray not exceed 50% of the cross sectional area of the cable tray (width x depth). TIA suggests a 40% fill ratio.
- *** Snake Tray series 201, 401, 454 and 501 are recommended to be supported every four (4) feet. However larger spans can be accommodated.



Snake Tray® products are covered by one or more of the following patents: #6637704, #6637165, #6463704, #6460812, #6449912, #6361000, #6347493, #6019323, #6347493, #6449912, #6460812, #5953870, #5839702, #6926236, #7168212, #7959019. Foreign Patents: Australia #737813, #748160, #749488, #776643, #776644. Canada #2251732, #2319624, #2303081, #2396792. Japan #3723224. Mexico #204995, #229386, #220889. Europe #1012938, 1012937. Other Patents Pending.

SNAKE TRAY®